



*North Group*  
*Machinery & Tools*





#### Especificaciones

Model		GH1440A
Max.Swing sobre cama	mm	Φ356(14')
Max.Swing.sobre carro	mm	Φ220(8-5/8')
Max.Swing.sobre escote	mm	Φ506(20')
ancho cama	mm	206(8')
Max. Distancia entre centros	mm	1000(40')
cono del Husillo		MT#5
Diametro de paso de barra	mm	Φ38(1-1/2')
Pasos de velocidades de husillo		16steps
Rango de Velocidades	r/min	45-1800rpm
Nariz de husillo		D-4
Rango de roscas metricas	mm	0.45-7.5(22kinds)
Rango de roscas pulgadas	TPI	4-112(40kinds)
ranfo de avances longitudina	mm	0.03-0.688(0.0011-0.0271'in/rev)
Rango de avances transversal	mm	0.015-0.220(0.0003-0.01'in/rev)
Diametro de Tornillo	mm	Φ22(7/8')
Paso de Tornillo	mm	4(8T.P.I)
Desplazamiento de Caña contrapunto	mm	120(4-3/4')
Diametro de caña Contrapunto	mm	Φ45(1-25/32')
Cono de Contrapunto		MT#3
Motor Principal	Kw	1.5/2.4
Peso Neto	Kg	960